

Caster Wheels

CW-250-250 Caster Wheel



- ★ 2-½ x 1-¼ Polyurethane Hi Tech Swivel Caster with a Threaded Stem & Side Lock Brake

Technical Specifications	
Load Capacity	250 lb. (Per wheel)
Wheel Width	1.25 in.
Wheel Bearing	Ball
Swivel Radius	2.4062 in.
Rig Material	Steel
Raceway	Double Ball
Thread Size	1/2-20
Stem Diameter	0.5 in.
Wheel Diameter	2.5 in.
Overall Height	3.75 in.
Axle Diameter	0.375
Stem Length	1.5 in.
Brake	Side Top Lock

Compatible with any of the following Load Cells:		
iLoad Pro 50 lb.- 1,000 lb.		

CW-250-350 Caster Wheel



- ★ 3-½ x 1-¼ Polyurethane Hi Tech Swivel Caster with a Threaded Stem & Side Lock Brake

Technical Specifications	
Load Capacity	250 lb. (Per wheel)
Wheel Width	1.25 in.
Wheel Bearing	Ball
Swivel Radius	2.9062 in.
Rig Material	Steel
Raceway	Double Ball
Thread Size	1/2-20
Stem Diameter	0.5 in.
Wheel Diameter	3.5 in.
Overall Height	4.5625 in.
Axle Diameter	0.375
Stem Length	0.75 in.
Brake	Side Top Lock

Compatible with any of the following Load Cells:		
iLoad Pro 50 lb.- 1,000 lb.		

CW-275-400 Caster Wheel



- ★ 4 x 1-¼ Polyurethane Hi Tech Swivel Caster with a Threaded Stem & Side Lock Brake

Technical Specifications	
Load Capacity	275 lb. (Per wheel)
Wheel Width	1.25 in.
Wheel Bearing	Ball
Swivel Radius	3.2187 in.
Rig Material	Steel
Raceway	Double Ball
Thread Size	1/2-20
Stem Diameter	0.5 in.
Wheel Diameter	4 in.
Overall Height	5 in.
Axle Diameter	0.375
Stem Length	0.75 in.
Brake	Side Top Lock

Compatible with any of the following Load Cells:		
iLoad Pro 50 lb.- 1,000 lb.		