

# Foot Pedals & Leveling Feet

## FP-1220 Foot Pedal



FP-325	Dimensions			
Material	Thread Size	Base Height	Total Height	Diameter
Stainless Steel	1/2-20 UNF	0.75 in. (19.1 mm)	2.62 in. (66.5 mm)	3.47 in. (88.1 mm)

Compatible with any of the following Load Cells:

iLoad Pro	iLoad TR
50 lb. - 2,500 lb.	2 lb. - 100 lb.

- ★ Replacement foot, adapts to most floor scales
- ★ Use with single-ended beams OR iLoad TR, iLoad Digital to provide large, flat, adjustable introduction surface
- ★ Special neoprene rubber sandwich base gives high accuracy, linearity and repeatability

## LF-1220 Leveling Foot



LF-325	Dimensions		
Material	Thread Size	Height	Foot Diameter
Zinc-Plated Steel	1/2-20 UNF	3.25 in. (82.55 mm)	1.87 in. (47.62 mm)

Compatible with any of the following Load Cells:

iLoad Pro	iLoad TR
50 lb. - 2,500 lb.	2 lb. - 100 lb.

- ★ Bright zinc and clear chromate plating for corrosion-resistance
- ★ Active ball suspension provided ideal load cell loading with maximum side load protection
- ★ Hardened alloy steel with plated finish
- ★ Includes two jamnuts, one for wrench access
- ★ Top of stud is machined undersized 10% for easy alignment into load cell plus one slotted for top-access applications


## LF-M6-F Self Leveling Foot



LF-M6-F	Dimensions		
Material	Thread Size	Height	Foot Diameter
Zinc-Plated Steel	M6 x 1	0.62 in. (16 mm)	0.74 in. (19 mm)

Compatible with any of the following Load Cells:

RSB4	REB7
10 kg. - 200 kg.	100 kg.



- ★ Metric Swivel Leveling Mount with Threaded Hole Zinc-Plated Steel, with Pad, M6 Thread
- ★ Safe Load: 515 lb.

## LF-M12-F Self Leveling Foot



LF-M12-F	Dimensions		
Material	Thread Size	Height	Foot Diameter
Zinc-Plated Steel	M12 x 1.75	1.25 in. (32 mm)	1.88 in. (48 mm)

Compatible with any of the following Load Cells:

RSB3
50 kg. - 500 kg.



- ★ Metric Swivel Leveling Mount with Threaded Hole Zinc-Plated STL, W/Pad, M12 Thread.
- ★ Safe Load: 3,740 lb.